



Most Beams Available in Lengths of: 20', 25', 30', 35', 40', 45', 50', 55', 60'

D Depth of Channel & Wt. Per Ft.	Wt For 20'	WT Thickness Of Web in Inches	WT Width Of Flange in Inches
3" X 5.7 lbs.	114	0.17	2.33
3" X 7.5 lbs.	150	0.349	2.509
4" X 7.7 lbs.	154	0.19	2.66
4" X 9.5 lbs.	190	0.326	2.796
5" X 10.0 lbs.	200	0.21	3
5" X 14.75 lbs.	295	0.494	3.284
6" X 12.5 lbs.	250	0.23	3.33
6" X 17.25 lbs.	345	0.465	3.565
7" X 15.3 lbs.	306	0.25	3.66
7" X 20.0 lbs.	400	0.45	3.86
8" X 18.4 lbs.	368	0.27	4
8" X 23.0 lbs.	460	0.441	4.171
10" X 25.4 lbs.	508	0.31	4.66
10" X 35.0 lbs.	700	0.594	4.944
12" X 31.8 lbs.	636	0.35	5
12" X 35.0 lbs.	700	0.428	5.078
12" X 40.8 lbs.	816	0.46	5.25
12" X 50.0 lbs.	1000	0.687	5.477
15" X 42.9 lbs.	858	0.41	5.5
15" X 50.0 lbs.	1000	0.55	5.64
18" X 54.7 lbs.	1094	0.46	6
18" X 70.0 lbs.	1400	0.711	6.251



STANDARD I BEAMS 

<b>D Depth of Channel &amp; Wt. Per Ft.</b>	<b>Wt For 20'</b>	<b>WT Thickness Of Web in Inches</b>	<b>WT Width Of Flange in Inches</b>
20" X 66.0 lbs.	1320	0.505	6.255
24" X 80.0 lbs.	1600	0.5	7
24" X 100.0 lbs.	2000	0.747	7.247
24" X 106.0 lbs.	2120	0.625	7.875